

09849386-050301
FOE050-98454860

5 **Method and Apparatus for Measuring and Classifying**
 Optically Observable Changes in Skin and Mucous Membrane

BACKGROUND OF THE INVENTION.

1. Field of the Invention.

10

The invention, in general, relates to a method and to an apparatus for measuring and classifying, in predetermined categories, optically observable changes in the skin and mucous membrane. More particularly, the invention relates to the measuring and classifying of such changes by endoscopic
15 observation.

15

A preferred field of application of the invention is the classification of skin anomalies such as, for examples, melanomata and melanotic changes in respect of benign, malignant or suspicious characteristics or properties. Other fields of
20 application are the classification of anomalies of skins and mucous membranes of endoscopically observable cavitory organs, such as the oesophagus, the stomach, the duodenum, the colon, the rectum, the bronchial system, the cavities of the throat, nose and ears as well as the bladder. Such anomalies may be, for instance, diverticula, adenoids, carbuncles, tumor infiltrations and
25 tumor compressions.

25

Malignant melanomata and the like may at the present time be identified with certainty in their late stage, when they are extremely dangerous and usually fatal. In their early stage, they may, however, be successfully treated in a

test area is irradiated by light of a second range of wavelengths, and a reference image is formed with light of the second wavelength range. By then scaling the values of intensity of the fluorescent image to those of the reference image, an image may be obtained in which the changes in intensity caused by the topology
5 are substantially eliminated and which is suitable for diagnosis by the treating physician.

Also, a fluorescent diagnosis device suitable for testing tumors in the internal wall of body cavities is known from German patent DE 198 19 516 A1.
10 Basically, the device consists of an endoscope and a camera for providing images of the test area on a monitor as well as of a spectrometer for spectrometrically examining the fluorescent light generated by selected sites of the test area. This diagnostic device does not, however, process the image to simplify the task of the diagnosing physician. Furthermore, the topology of the
15 tested tissue area has no effect upon the diagnosis.

WO9747235 discloses a diagnostic system and method suitable for quantifying the visual appearance of skin anomalies, such as melanomata, by digitally analyzing images of the skin. In a preferred embodiment, the system
20 includes a high-resolution digital camera, a computer, a data storage as well as a color monitor. The camera generates an image of the skin area to be examined, as well as, close to the area of the skin to be examined, of a longitudinal scale and of a color scale. This makes it possible to scale color values and spacings in the image independently of illumination and exposure conditions. The
25 computer defines and subsequently displays on the monitor, the external contour of dark skin areas. Also, characteristic values of the color of the examined skin area as well as two-dimensional geometric characteristic values such as size and asymmetry of the external contour of dark skin areas may be derived, and characteristic values and images generated at different times may be compared,

by the diagnostic system. Even though the diagnostic system of WO9747235 provides different characteristic values of geometry and color, an identification of skin anomalies is nevertheless strongly dependent upon the experience of the examining physician.

5

For rendering the classification of skin anomalies more objective and for automating it, it is known for purposes of classification to process difference characteristics of skin anomalies such as shape and color in color images of a skin area by a neuronal net (Ercal, F.: et al., IEEE Transactions on Biomedical Engineering, (1994 Sep.) 41(9) 837-45). For classification, the method strongly relies upon the processing of characteristic values of color as well as upon the asymmetry and irregularities of the marginal contour of a skin anomaly. The method does not make use of the size or the diameter of a skin anomaly, or of their changes over time, as characteristic values during the classification process, and it requires a very precise definition of the margins of skin anomalies which for that reason is performed by a dermatologist.

Another example of the use of a neuronal net for classifying tumors in ultrasound images has been described in U.S. Patent 5,260,871. In this case, characteristic values are extracted from the ultrasound images and input into the neuronal net which performs a classification. This solution, too, does not evaluate data relating to the three-dimensional structure of a suspicious area of tissue.

25 An essential disadvantage of known solutions resides in the fact that no data about the three-dimensional structure of suspicious tissue areas is being evaluated and used for purposes of classification. It has, however, been shown that for evaluating melanoma examinations, three-dimensional structure and growth in height are important criteria for determining the property of

melanomata.

OBJECTS OF THE INVENTION.

5 Accordingly, it is an important object of the invention to provide a method and an apparatus suitable for measuring optically observable changes of skin and mucous membrane and which include the three-dimensional structure of such changes and their changes over time as important classification characteristics.

10

 It is another object of the invention to measure and classify skin anomalies such as melanomata and melanoma-like symptoms by taking into consideration their three-dimensional and temporal changes.

15 BRIEF SUMMARY OF THE INVENTION.

 As used herein, the term "skin" is intended to connote not only the external skin but also mucous membranes of a person or animal.

20

 In accordance with a currently preferred embodiment the invention provides for a method of measuring and classifying optically observable changes in skin by, firstly, taking and recording at least one image of a change in the skin suitable for defining the three-dimensional structure and color structure and at least one reference image of at least the vicinity of the change, by, secondly,
25 computing the surface measurements of the changes in skin consisting of the three-dimensional coordinates of the changes and of their associated color values scaled to the reference image and of, optionally, computing the changes over time, by, thirdly, performing a classification, preferably by means of a neuronal net, on the basis of the computed surface measurements together,

optionally, with other data relevant to a patient such as age, type of skin, allergies, dermatoscopic or sonographic diagnoses, by, thirdly, performing another classification, particularly in a case which defies certain classification, on the basis of the previously obtained data but differing from the previous

- 5 classification by the use of a modified algorithm and/or by using a selection of comparative data, preferably evaluated by experts, stored in at least one data base, and by, fourthly, issuing the results of the classification yielded by the third and fourth operations.

- 10 The apparatus in accordance with the invention preferably includes a measuring head or cameras for generating at least two photogrammetrically evaluatable images of changes in skin and a pattern projector for projecting onto the area of the skin to be examined a pattern suitable for detecting three-dimensional data of the area, at least one of the cameras being suitable for
- 15 recording as reference images for defining a reference color images of an area of healthy skin in the vicinity of the changed skin, a first computer for preparing, processing and storing the images generated by the measuring head and, more particularly, for computing surface data of a change consisting of the three-dimensional coordinates of the change and the associated color values scales to
- 20 the reference image, and for computing changes over time of these data, a second computer for executing a first classification of any changes on the basis of the surface measurement data and, optionally, of the stored relevant data relating to a patient such as age, type of skin, allergies, dermatoscopic or sonographic diagnoses, etc., optionally, a third computer for performing, with a
- 25 modified algorithm and/or a selection from a data base of comparative data evaluated by experts, a further classification, particularly in the case of defying certain classification, on the basis of the surface measurement data and, optionally, of the stored relevant data relating to the patient.

1 The method of the invention is based upon the concept of generating in
intervals of times appropriate for a diagnosis and by means of suitable recording
techniques, such digital images of changes of the skins to be examined and
optically observable which can be evaluated in respect of the three-dimensional
5 structure of the depicted subject as well as of its color structure. A recording
technique suitable for this purpose is known from the present inventors' German
patent 196 23 172.

10 In a first operational step, the surface measurement data of changes in
the skin and mucous membrane are computed from the digital images. The data
consists of the three-dimensional coordinates and the associated color values
scaled to the reference image. Optionally, the changes over time of the changes
are additionally computed.

15 In a second operational step, the surface measurement data are
evaluated, preferably by a neuronal net, by a process of classification. The
result will be a classification into, for instance, benign, suspicious or malignant
changes.

20 If it is not possible to obtain a certain classification on the basis of the
image material provided in accordance with the invention and the surface
measurement data derived therefrom, a third operational step will be performed
in accordance with another basic concept of the invention. The third operational
step comprises a classifying process differing from the previous one by a
25 modified algorithm and/or by the use of a selection of comparative data,
preferably evaluated by experts, stored in at least one data base.

In this data base, evaluated histories of diseases are documented by
images recorded at different dates and by three-dimensional data as well as by

data relevant to the disease. It is of utmost importance that the records of these histories of diseases have been classified with a very high degree of certainty, frequently by histological examinations. Instead of the classification of the changes in skin and mucous membrane, or in addition to the classification, an

5 artificial neuronal net connected to the data base may can select comparative material from the data base, i.e., histories of diseases of changes in skins and mucous membranes the physical properties and appropriate relevant data of which are comparable to the changes in the skin and or mucous membrane to be examined. From the selected comparative data suitable images including

10 evaluations which are similar to the input data may be selected and returned to the treating physician.

Execution of the operational steps is possible in the following variations:

- ◆ all operational steps are being performed on a local computer;
- 15 ◆ the first and the second operational step are performed on a local computer and the third operational step is performed by a central computer;
- ◆ the first operational step is performed on a local computer and the second and third operational steps are performed on a central computer;
- 20 ◆ all of the operational steps are performed on a central computer.

In accordance with a further advantageous embodiment of the inventive method at least one of the data bases containing comparative data evaluated by experts is disposed and maintained on the central computer, the local computer

25 having access to the central computer.

The apparatus in accordance with the invention comprises two major components: A measuring head for generating at least to photogrammetrically evaluatable images of the changes in the skin to be examined and classified and

at least one computer connected to the measuring head by way of data lines or integrated into the measuring head.

The measuring head is provided with at least two calibrated cameras, hereinafter sometimes referred to as camera group, for generating digital images of the area to be examined, and with a pattern projector for projecting onto the area to be examined at least one pattern suitable for detecting three-dimensional data of the said area. The camera group is adjusted such a surface of appropriate size may be measured by it. At least one of the cameras of the camera group is adapted for taking color images, this camera or, optionally, a further camera, being additionally provided for taking, as a reference image for defining a reference color, an image of an inconspicuous area in the vicinity of the change in the skin. The measuring head is movable and may be positioned at an appropriate location.

The at least one computer connected to the measuring head by way of data lines is provided with means for preparing, processing and storing the digital images of the skin and mucous membrane changes generated by the measuring head. Such means may include means for computing data of the three- and two-dimensional structures of the changes and their color structures relative to the reference image as well as of the temporal changes of the said data. The computer is additionally provided with means for carrying out a classification on the basis of the previously mentioned detected data and, if necessary, the relevant data relating to a patient such as age, type of skin, allergies, dermatoscopic or sonographic diagnoses etc. A neuronal net may be used to provide such classification.

For use in connection with a case which cannot be classified with certainty, the computer is preferably provided with means for carrying out a

further classification with a modified algorithm and/or a selection of comparative data evaluated by experts, on the basis of the previously detected data and, if necessary, the relevant patient-related data stored in a data base.

- 5 In an advantageous embodiment of the device in accordance with the invention there are provided at least two computers interconnected by data lines. At least one of the computers is a local one and at least one other computer is a central one. In such a case only the central computer is provided with the means applied in a case which cannot be classified with certainty such as, in particular,
10 the data base of comparative data evaluated by experts.

DESCRIPTION OF THE DRAWING.

- The novel features which are considered to be characteristic of the
15 invention are set forth with particularity in the appended claims. The invention itself, however, in respect of its structure, construction and lay-out as well as manufacturing techniques, together with other objects and advantages thereof, will be best understood from the following description of preferred embodiments when read in connection with the appended single drawing which is a flow
20 diagram schematically depicting the cooperation between the operational steps in accordance with the invention.

- The example shown relates to the classification of skin anomalies known as melanoma and melonocytic changes into suitable categories such as, for
25 instance, benign, suspicious or malignant.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS.

The measuring head comprises a camera group of two calibrated color

patterns are projected onto the skin anomaly by the pattern projector. Such light patterns are indispensable to the process.

5 The recorded digital images or image sequences form the basis of the
computation of the data relating to the three- and two-dimensional structures of
the skin anomaly and its color structure relative to the reference image. To this
end, a local computer, proceeding from the recorded digital images, computes in
a first process or operational step surface measurement data of the skin
anomaly. The surface measurement data consist of the three-dimensional
10 coordinates and associated scaled color values of the surface of the skin
anomaly.

15 The images or image sequences of the skin anomaly taken with the light
patterns are used to define the three-dimensional coordinates. Known or novel
algorithms used in image processing are used for the computation. The
algorithms are based on the definition of corresponding pairs of pixels by
matching processes or by correlation algorithms.

20 The light image and the reference image are used to define the scaled
color values of the skin anomaly. The color values of the light image are affected
by the activity of the skin anomaly as well as by the basic complexion of the skin
(depending on a seasonally conditioned degree of tanning). To minimize the
effect of the last-mentioned affect scaling relative to the reference image is
useful. Scaling may be carried out in the conventionally (use of an offset and
25 lightness correction) or by the neuronal net manner. The result will be scaled
color values. Correlating the scaled color values to the three-dimensional
coordinates is simple since both data are defined on the basis of images from
the same cameras in the same positions.

09049386 050304
T0E050" 98E64960

10 The surface measurement data of the skin anomaly determined in this manner are subjected in a second operational step also performed on a local computer to a first classification process by means of a neuronal net. This results in a correlation of appropriate categories, e.g., benign, malignant or
5 suspicious. This result and the surface measurement data obtained are well suited for documentation and archiving in a patient data base. If measurements are taken at different times, the relevant changes of the surface measurement data of the skin anomaly can be determined from the documentation.

10 In order further to improve the quality of classification a telematic system may optionally be utilized. In such a system the surface measurement data of the skin anomaly measured by the treating physician are transferred to a central computer and correlated to or compared with relevant patient related data obtained elsewhere, such as age, type of skin, allergies, dermatoscopic or
15 sonographic diagnoses and so forth.

A third operational or process step may then be carried out on the central computer. The third step consists of a further classification based on modified algorithms and/or a selection of suitable comparative data from at least one data
20 base.

The data base may be a central data base stored in a central computer. Alternatively or additionally, the data base may be an external data base which may for instance be accessible through the Internet.

25 Such data banks contain evaluated histories of diseases documented by images and surface measurement data recorded at different times as well as relevant patient-related data (described *supra*) relevant to the disease. It is decisive that these disease histories have been classified with a high degree of

certainty, often by histological examinations.

On the basis of data stored in the mentioned data bases the artificial neuronal net or another suitable algorithm of the central computer will detect skin anomalies the surface measurement data of which are sufficiently similar to the skin anomaly measured by the treating physician and transferred to the central computer. The patient-related data are also considered. In this manner, it is possible to obtain suitable comparative data such as evaluated images and optional additional data such as histological diagnoses and other data of interest from the history of disease. They are returned to the treating physician. They serve to improve the result of the classification.

Another telematic application resides in consulting an expert to whom the surface measurement data, the result of the classification and relevant patient-related data are submitted by data lines. Such consultation may be carried out in the manner of video conferencing.

Further possibilities of use of the inventive method and apparatus arise in connection with the following problems:

- ◆ The measuring head may be utilized for augmenting diagnoses of other diseases in the field of dermatology. A typical application resides in the measuring and evaluation of skin rashes. Another application is the measuring changes of color and height caused by allergy tests. Precise documentation is made possible by the measuring head.
- ◆ For documenting and evaluating the healing progress of wounds measurements may be very useful. To this end, two-dimensional and three-dimensional data as well as the color structure are measured at one

or more points in time. Analogously, measurements may be taken of skin burns where a precise definition of the degree of burn is of importance.

- 5 ♦ Radiation treatments may also result in changes in the skin color of a patient. Where such changes are measured it is possible to arrive at conclusions as to the radiation sensitivity of the patient.
- 10 ♦ The measuring head may also be used for measuring and evaluating skin creases or wrinkles (primarily in a face). This may be important to the cosmetics industry in connection with determining, for instance, the effectiveness of skin creams and lotions.

What is claimed is:

15

20

25

10E050" 98E64860